01. Installation

```
services:
  app:
    build:
      context: .
    image: invoiceninja/invoiceninja-debian:latest
    restart: unless-stopped
    env_file:
      - ./.env
    volumes:
      - ./app_public:/var/www/html/public
      - ./app_storage:/var/www/html/storage
    depends_on:
      mysql:
        condition: service_healthy
      redis:
        condition: service_healthy
  nginx:
    image: nginx:alpine
    restart: unless-stopped
    ports:
      - 8333:80
      - 6443:443
    volumes:
      - ./nginx:/etc/nginx/conf.d:ro
      - ./app_public:/var/www/html/public:ro
      - ./app_storage:/var/www/html/storage:ro
    depends_on:
      app:
        condition: service_healthy
  mysql:
    image: mysql:8
    restart: unless-stopped
    environment:
      MYSQL_DATABASE: ${DB_DATABASE}
      MYSQL_USER: ${DB_USERNAME}
```

```
      MYSQL_PASSWORD: ${DB_PASSWORD}
      MYSQL_ROOT_PASSWORD: ${DB_ROOT_PASSWORD}
    volumes:
      - ./mysql_data:/var/lib/mysql
    healthcheck:
      test:
        - CMD
        - mysqladmin
        - ping
        - -h
        - localhost
        - -u${MYSQL_USER}
        - -p${MYSQL_PASSWORD}
  redis:
    image: redis:alpine
    restart: unless-stopped
    volumes:
      - ./redis_data:/data
    healthcheck:
      test:
        - CMD
        - redis-cli
        - ping
networks: {}
```

```
# IN application vars
APP_URL=https://invoice.rfeyn.org
APP_KEY=base64:oUr5FRUWNrM42GeyksHF33ntNtlh29KW5vg2J2brnJ4=
APP_ENV=production
APP_DEBUG=true
REQUIRE_HTTPS=false
PHANTOMJS_PDF_GENERATION=true
PDF_GENERATOR=snappdf
TRUSTED_PROXIES='*'



CACHE_DRIVER=redis
QUEUE_CONNECTION=redis
SESSION_DRIVER=redis
```

```
REDIS_HOST=redis
REDIS_PASSWORD=null
REDIS_PORT=6379

FILESYSTEM_DISK=debian_docker

# DB connection
DB_HOST=mysql
DB_PORT=3306
DB_DATABASE=ninjadplancer
DB_USERNAME=ninja
DB_PASSWORD=sf9823fsjlfkjwioefjlskfh0923jfklsdjf
DB_ROOT_PASSWORD=sdpoifj293fj09030rjnsnedfo3498t
DB_CONNECTION=mysql

# Create initial user
# Default to these values if empty
IN_USER_EMAIL=dp@p2pnode.org
IN_PASSWORD=nvQi5W14blOnpv
# IN_USER_EMAIL=
# IN_PASSWORD=

# Mail options
MAIL_MAILER=log
MAIL_HOST=smtp.porkbun.com
MAIL_PORT=587
MAIL_USERNAME=dp@p2pnode.org
MAIL_PASSWORD=PuV9#@pUca49C70e2V46&keg
MAIL_ENCRYPTION=tls
MAIL_FROM_ADDRESS='dp@p2pnode.org'
MAIL_FROM_NAME="DPLancer Invoices"

# MySQL
MYSQL_ROOT_PASSWORD=sdpoifj293fj09030rjnsnedfo3498t
MYSQL_USER=ninja
MYSQL_PASSWORD=sf9823fsjlfkjwioefjlskfh0923jfklsdjf
MYSQL_DATABASE=ninjadplancer

# GoCardless/Nordigen API key for banking integration
NORDIGEN_SECRET_ID=
```

```
NORDIGEN_SECRET_KEY=


IS_DOCKER=true
SCOUT_DRIVER=null
#SNAPPDF_CHROMIUM_PATH=/usr/bin/google-chrome-stable
```

Revision #1
Created 2026-07-05 23:56:15 UTC by dpasn
Updated 2026-07-05 23:56:15 UTC by dpasn