# Homeserver.yaml

```
# DO NOT USE THIS CONFIGURATION FILE FOR PRODUCTION

server_name: "dgroningen.org"
public_baseurl: "https://matrix.dgroningen.org/"

pid_file: /data/homeserver.pid
listeners:
  - port: 8008
    tls: false
    type: http
    x_forwarded: true
    resources:
      - names: [client, federation]
        compress: false
database:
 name: psycopg2
 args:
   user: synapse_user
   password: skjsdf9834jf3j9j4598t3498j3908fn983yv3
   database: synapse
   host: synapse-db
   cp_min: 5
   cp_max: 10
log_config: "/data/matrix.yourdomain.com.log.config"
media_store_path: /data/media_store
registration_shared_secret: "YRGKetN~MIoXWrqJGTkLaY2.3n0#UDClRF1oteAEk7mWq=1f95" # DO NOT USE
THIS
report_stats: false
macaroon_secret_key: "#stDom~z;7M_Fjd0o,Mtn7BFOdIUqb5~DUg4;ipSo+6xEzuV#i" # DO NOT USE THIS
form_secret: ":ANf04Ysn5mh^1PdRHOXe3tT01NERDtBRYHMStkjUu.^wO@mUU" # DO NOT USE THIS
signing_key_path: "/data/matrix.yourdomain.com.signing.key"
trusted_key_servers:
  - server_name: "matrix.org"

################################Custom Data that can be copied amongst
```

```
instances#####################################

enable_registration: true
# users require an email to sign up - needed for password resets
registrations_require_3pid:
  - email
#enable_registration_captcha: true
#recaptcha_public_key: <recaptcha site key>
#recaptcha_private_key: <recaptcha private key>

email:
  # The hostname of the outgoing SMTP server to use. Defaults to 'localhost'.
  #
  smtp_host: smtp.porkbun.com

  # The port on the mail server for outgoing SMTP. Defaults to 25.
  #
  smtp_port: 587

  # Username/password for authentication to the SMTP server. By default, no
  # authentication is attempted.
  #
  smtp_user: "dp@p2pnode.org"
  smtp_pass: "PuV9#@pUca49C70e2V46&keg"

  # Uncomment the following to require TLS transport security for SMTP.
  # By default, Synapse will connect over plain text, and will then switch to
  # TLS via STARTTLS *if the SMTP server supports it*. If this option is set,
  # Synapse will refuse to connect unless the server supports STARTTLS.
  #
  require_transport_security: true

  # notif_from defines the "From" address to use when sending emails.
  # It must be set if email sending is enabled.
  #
  # The placeholder '%(app)s' will be replaced by the application name,
  # which is normally 'app_name' (below), but may be overridden by the
  # Matrix client application.
  #
  # Note that the placeholder must be written '%(app)s', including the
```

```
  # trailing 's'.
  #
  notif_from: "Your Friendly %(app)s homeserver <noreply@yourdomain.com>"

  # app_name defines the default value for '%(app)s' in notif_from and email
  # subjects. It defaults to 'Matrix'.
  #
  app_name: DGroningen

  # Uncomment the following to enable sending emails for messages that the user
  # has missed. Disabled by default.
  #
  #enable_notifs: true

  # Uncomment the following to disable automatic subscription to email
  # notifications for new users. Enabled by default.
  #
  notif_for_new_users: true

# allows people to change their email address
enable_3pid_changes: true
# allows searching of all users in directory
user_directory.search_all_users: true
# allow room access over federation
matrix_synapse_allow_public_rooms_over_federation: true
# enable federation on port 443
serve_server_wellknown: true



# vim:ft=yaml
```

---

Revision #2
Created 2026-06-03 00:48:15 UTC by dpasn
Updated 2026-06-03 00:57:56 UTC by dpasn