

Homeserver.yaml

```
# DO NOT USE THIS CONFIGURATION FILE FOR PRODUCTION

server_name: "dgroningen.org"
public_baseurl: "https://matrix.dgroningen.org/"

pid_file: /data/homeserver.pid
listeners:
  - port: 8008
    tls: false
    type: http
    x_forwarded: true
    resources:
      - names: [client, federation]
        compress: false
database:
  name: psycopg2
  args:
    user: synapse_user
    password: skjsdf9834jf3j9j4598t3498j3908fn983yv3
    database: synapse
    host: synapse-db
    cp_min: 5
    cp_max: 10
log_config: "/data/matrix.yourdomain.com.log.config"
media_store_path: /data/media_store
registration_shared_secret: "YRGKetN~MIoXWrqJGTkLaY2.3n0#UDClRF1oteAEk7mWq=1f95" # DO NOT USE THIS
report_stats: false
macaroon_secret_key: "#stDom~z;7M_Fjd0o,Mtn7BF0dIUqb5~DUg4;ipSo+6xEzuV#i" # DO NOT USE THIS
form_secret: ":ANf04Ysn5mh^1PdRH0Xe3tT01NERDtBRYHMStkjUu.^w0@mUU" # DO NOT USE THIS
signing_key_path: "/data/matrix.yourdomain.com.signing.key"
trusted_key_servers:
  - server_name: "matrix.org"

#####Custom Data that can be copied amongst
```

```
instances#####
```

```
enable_registration: true
```

```
# users require an email to sign up - needed for password resets
```

```
registrations_require_3pid:
```

```
- email
```

```
#enable_registration_captcha: true
```

```
#recaptcha_public_key: <recaptcha site key>
```

```
#recaptcha_private_key: <recaptcha private key>
```

```
email:
```

```
# The hostname of the outgoing SMTP server to use. Defaults to 'localhost'.
```

```
#
```

```
smtp_host: smtp.porkbun.com
```

```
# The port on the mail server for outgoing SMTP. Defaults to 25.
```

```
#
```

```
smtp_port: 587
```

```
# Username/password for authentication to the SMTP server. By default, no
```

```
# authentication is attempted.
```

```
#
```

```
smtp_user: "dp@p2pnode.org"
```

```
smtp_pass: "PuV9#@pUca49C70e2V46&keg"
```

```
# Uncomment the following to require TLS transport security for SMTP.
```

```
# By default, Synapse will connect over plain text, and will then switch to
```

```
# TLS via STARTTLS *if the SMTP server supports it*. If this option is set,
```

```
# Synapse will refuse to connect unless the server supports STARTTLS.
```

```
#
```

```
require_transport_security: true
```

```
# notif_from defines the "From" address to use when sending emails.
```

```
# It must be set if email sending is enabled.
```

```
#
```

```
# The placeholder '%(app)s' will be replaced by the application name,
```

```
# which is normally 'app_name' (below), but may be overridden by the
```

```
# Matrix client application.
```

```
#
```

```
# Note that the placeholder must be written '%(app)s', including the
```

```
# trailing 's'.
#
notif_from: "Your Friendly %(app)s homeserver <noreply@yourdomain.com>"

# app_name defines the default value for '%(app)s' in notif_from and email
# subjects. It defaults to 'Matrix'.
#
app_name: DGroningen

# Uncomment the following to enable sending emails for messages that the user
# has missed. Disabled by default.
#
#enable_notifs: true

# Uncomment the following to disable automatic subscription to email
# notifications for new users. Enabled by default.
#
notif_for_new_users: true

# allows people to change their email address
enable_3pid_changes: true
# allows searching of all users in directory
user_directory.search_all_users: true
# allow room access over federation
matrix_synapse_allow_public_rooms_over_federation: true
# enable federation on port 443
serve_server_wellknown: true

# vim:ft=yaml
```

Revision #2

Created 2026-06-02 22:48:15 UTC by dpasn

Updated 2026-06-02 22:57:56 UTC by dpasn